

BED MAKING MACHINE



BEDDY

BEDDY

WHAT IS BEDDY?



BEDDY is machine intended for presowing soil preparation in form of tiling and bed shaping.

HOW DOES BEDDY WORKS?



Tilling section shreds, mixes and crumble soil, preparing it for bed shaping operation.

Soil containment elements (profilers) of the bed making section forms bed distributing loose soil prepared by tilling section of the machine.

BENEFITS OF USING



- **Easy handling**
- **Robust construction**
- **Trusted functionality**
- **High performance**
- **Reduces costs**
- **High level of personalisation**



MACHINE FEATURES

➤ TILLING SECTION

- Fits machines with Cat 1 and 2, 3-Point hoop-up
- Spiral placed blades results with lesser requirement for power and finest tilling
- 4 blades per flange (possibility for 6 blades per flange as additional option)
 - Adjustable working depth
 - Maximal working (tilling) depth of 18 cm



MACHINE FEATURES

➤ TILLING SECTION

- PTO shaft speed: 540 o/min
- Shaft rotation speed: 238 o/min
 - Gearbox power - 48 kW
- Power (driving) chain in oil bath
- Possibility of performing only tilling operations – without bed making operations

MACHINE FEATURES

➤ BED MAKING SECTION



- Soil containment elements (profilers) makes bed by distributing soil prepared by tilling section of the machine.
- Compaction of the soil in bed is enabled (and regulated) by spring system placed on upper part of the bed making section.



BEDDY MACHINE MODELS

Gredičar za povrće
RTB7618



Gredičar za povrće
RTB7623





BEDDY MACHINE MODELS

- PURPOSES

Models of machines are derived according to the size of bed that each version of machine can create

Intended (suggested) purpose of models:

- 1. RTB7618 - intended for single season plants**
- 2. RTB7623 - intended for multi seasonal plants (e.g. strawberries)**



MODEL RTB7618

	RTB7618
Transport width (mm)	1860
Working width (mm)	1500
Length (mm)	1030
Height (mm)	1150
Bed width (mm)	760
Bed height (max mm)	180
Demanded power (min KS)	40 - 65
Foil laying width (min mm)	1200



MODEL RTB7623

	RTB7623
Transport width (mm)	1860
Working width (mm)	1500
Length (mm)	1030
Height (mm)	1150
Bed width (mm)	760
Bed height (max mm)	230
Demanded power (min KS)	50 - 75
Foil laying width (min mm)	1400



ADDITIONAL EQUIPMENT –

FOIL LAYING SYSTEM

- **Removable and adaptable foil carrier that can receive foil**
- **Built-in mechanism that prevents unwanted unrolling of the foil**



**ADDITIONAL EQUIPMENT –
ON GROUND IRRIGATION (DRIP)**

HOSE LAYING SET

Allows laying up to 2 irrigation drip hose on ground (on previously formed bed) while foil is being laid.

By using this set irrigation (drip) hose is placed between soil and foil that is being laid.



ADDITIONAL EQUIPMENT -

**FERTILIZER ATTACHMENT WITH
STAINLESS STEEL HOPPER**

Allows fertilisation of soil while bed is being created, meaning fertilizer is dropt on soil and buried during bed forming operations.

Hopper is made of stainless steel.

Dispersing is propelled by electromotor.

Spreading quantity regulated by combination of setups on electric cabin control unit, mechanical regulator and tractor moving speed.



ADDITIONAL EQUIPMENT –

PUNCH WHEEL SYSTEM

Main purpose is to punch holes on the layed foil in which plans will be transplanted.

Zink coated/galvanized

Depending of customer needs, system can contain 1 wheel (punching holes in 1 row), 2 wheels (punching holes in 2 rows) or even 3 wheels (punching holes in 3 rows).

- **Manufactured in Croatia**
- **Machine is of European origin**



Klik ili scan za pregled



If you have any interest of purchasing this machine of ours,
be free to contact us.

Sincerely yours, Agroservis – proizvodnja d.o.o. team

Address:

Stjepan Radic street
No. 136
33000 Virovitica
R. Hrvatska /
Croatia

Phone:

+385 (0)99 254 8233

+385 (0)33 730 240

Mr. Kovač Andrej

e-mail:

agroservisproizvodnja.vt@gmail.com

agroservis.proizvodnja@vt.t-com.hr

*All pictures and illustrations shown in this file are for illustration purpose only. Actual product may vary due to product enhancement.